




TECHNICAL DATA

GENERAL		C 400 H x4
Load capacity to 24"	lb	8,000
Unladen weight *	lb	16,314
Transmission		Hydrostatic, with continuous speed control
MAST		
Fork carriage		FEM III
Carriage width	in	65.35
ENGINE		
Make		DEUTZ
Model		TD3.6
Power	hp	74.2
Operating speed	r/min	2,200
Torque	Nm@rpm	330@1600
No. cylinders		4
Emissions		Stage IIIB + EPA/CARB Tier4
Ambient noise	dB(A)	104
DRIVING		
Max. speed	mph	12.4
Gradeability	%	35
Traction		4x4 FullGrip®
Front tires		18-19.5
Rear tires		10.0/75-15.3
HYDRAULIC SYSTEM		
Hydraulic circuit	gal/min	15.6
Working pressure	psi	3,190
TANK CAPACITY		230
Fuel	gal	31.7
Hydraulic	gal	25.1
BRAKES		
Service		Hydraulic, multi-disc and sealed
Parking		Mechanical, multi-disc and sealed

* It may change due to optional equipment

DIMENSIONS

TYPE OF MAST	Maximum lift (ft)	H Retracted mast height (in)	Extended mast height (in)	Free lift (in)	Load at maximum height @ 24" All-terrain use (lb)
Duplex mast (Std.)	12.14	108.2	180.5	3.9	8,000
Triplex mast	13.94	92.5	207.1	54.8	8,000
Triplex mast	17.88	108.2	254.3	70.6	4,800



DIMENSIONS (in)	C 400 H x4
A	91.7
B	10.6
C	11.4
D	66.2
E	78.2
F	175.2
G	124.8
I	4.7
J	1.9
K	28.3
L	181.9
M	25.6
N	80.7
O	47.2
P	258.6
S	65.3
DIMENSIONS (°)	
Q	10
R	10



www.ausa.com

Products are subject to modifications without prior notice. Images throughout the spec sheet may refer to non-standard machines or non-available configurations depending on models.

AUSA's logo and corporate identity are property of the Company, they cannot be used without authorization.